

Product description

Model with bipolar protective diode. Monitoring contact as potential-free changeover contact, actuated by the latch bolt. This model can also be permanently unlocked mechanically (daytime unlocking).

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Voltage range
- Compatible with current mortise locks
- Compatible with ProFix® 2 strike plates
- Optimal latch ramps for gentle interaction with the latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

DIN-direction	Universal
	10-24 V AC/DC
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Bi-directional diode	Yes
Switching capacity - monitoring contact	24 V / 1 A
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
Current consumption 12 V AC	250 mA
Load cycles for in-plant test	250000
Installation position	Vertical and horizontal
Operating temperature range	-15 °C to +40 °C
Break-in resistance	3750 N
Height	74 mm
Suitable for fire doors	No
Depth	26 mm
Latch bolt engaging depth	5.5 mm
Width	20.1 mm
FaFix® adjustment range	3 mm
Max. preload 12 V AC	200 N
Max. preload 12 V DC (stabilised)	50 N
Max. preload 24 V AC	350 N
Max. preload 24 V DC (stabilised)	200 N

Article number 118E.63- - - - A71

EAN 4042203406001

