

Product description

Model with monitoring contact as potential-free changeover contact, actuated by the latch bolt. Suitable for fire rated doors.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Voltage range
- Compatible with DIN 18250 mortise locks
- Compatible with ProFix® 2 strike plates
- Optimal latch ramps for gentle interaction with the latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable
- Bipolar diode

Scope of delivery

- 1 piece electric strike

Technical data

DIN-direction	Universal
	10-24 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-locked	Yes
Bi-directional diode	Yes
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Switching capacity - monitoring contact	24 V / 1 A
Current consumption 12 V AC	250 mA
Current consumption 12 V DC (stabilised)	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC (stabilised)	560 mA
Break-in resistance	9000 N
Height	74 mm
Width	20.1 mm
Depth	25.5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	6 mm
Operating temperature range	-15 °C to +40 °C
Load cycles for in-plant test	250000
Installation position	Vertical and horizontal
Suitable for fire doors	Yes
Certified in compliance with	DIN EN 14846:2008
Max. preload 12 V DC (stabilised)	50 N
Max. latch preload DC (stabilised)	50 N
Max. preload 24 V DC (stabilised)	200 N
Max. latch preload AC	200 N
Max. preload 24 V AC	> 350 N
VdS-approval	Z114003

Article number 118F.23-----A71

EAN 4042203417410

