

Electric strike 118S-----A71

effeff Smoke Protection Electric Strike 118 with FaFix® (FF)

Product description

Model with basic equipment.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Voltage range
- Compatible with DIN 18250 mortise locks
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

| | |
|--|-------------------------|
| DIN-direction | Universal |
| | 10-24 V AC/DC |
| Adjustable keeper (FF, FaFix®) | Yes |
| Fail-locked | Yes |
| Continuous duty | 11-13 V DC |
| Rated resistance | 43 Ohm |
| Current consumption 12 V AC | 250 mA |
| Current consumption 12 V DC (stabilised) | 280 mA |
| Current consumption 24 V AC | 500 mA |
| Current consumption 24 V DC (stabilised) | 560 mA |
| Break-in resistance | 3750 N |
| Height | 66 mm |
| Width | 16 mm |
| Depth | 25.5 mm |
| FaFix® adjustment range | 3 mm |
| Latch bolt engaging depth | 5.5 mm |
| Operating temperature range | -15 °C to +40 °C |
| Load cycles for in-plant test | 250000 |
| Installation position | Vertical and horizontal |
| Suitable for fire doors | No |
| Certified in compliance with | EN 14846:2008 |
| Max. latch preload DC (stabilised) | 50 N |
| Max. latch preload AC | 200 N |

Article number 118S-----A71

EAN 4042203393981

