

### Product description

Model with basic equipment.

### Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Voltage range
- Connection available to order as a connectible/pluggable option
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

### Scope of delivery

- 1 piece electric strike

### Technical data

DIN-direction	Universal
Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Current consumption 12 V AC	250 mA
Current consumption 12 V DC (stabilised)	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC (stabilised)	560 mA
Break-in resistance	3750 N
Height	66 mm
Width	16 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5.5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Max. latch preload AC	200 N
Max. latch preload DC (stabilised)	50 N
Suitable for fire doors	No
Depth	25.5 mm

Article number	118- - - - - A71
EAN	4042203339064

